## 8,500 DWT DIESEL-ELECTRIC GENERAL CARGO VESSEL

Multi-purpose dry cargo vessel with diesel electric propulsion, with engines running in accordance with IMO Tier III. The single fixed pitch propeller has an optimum diameter, in combination with optimized hull lines and design, for a fuel-efficient speed-power performance powered by a future proof modular electric propulsion system.

				BOOMSMASHIPPINGAL	
Main Particulars		Main Engine	NA	Cargo Hold	
Length Overall	113.37 m			Hold Capacity	520,360 cubic feet
Length Between Perpendiculars	109.58 m	<b>Generators (IMO Tier III)</b>		Hold-1 Dimensions	72.10 x 15.50 m
Breadth, Moulded	18.60 m	Main Diesel Generators	4 Sets x 556 KWe	Hold-2 Dimensions	13.80 x 11.28 m
Depth to Main deck	11.80 m		1500 - 1800 RPM		
Designed Draught	6.85 m	Emergency Generator	1 Set x 120 KWe	Container Capacity	488 TEU
Deadweight	8,500 T		1500 RPM	Hold	272 TEU
Gross Tonnage	7,327 GT			On Hatches	216 TEU
The state of the s		Propulsion & Steering		8	
<u>Complement</u> 9 Persons		FPP System		Hatch Covers & Crane	
		1 x Nozzle		Covers Pont	oon Type Hatch Covers
<u>Maximum Speed</u>	10.5 knots	2 x 975 bKW Propulsion Motors 1 x Flap Type Spade Rudder		Crane	1 x 18.5 T SWL Crane
(17)					
Classification		1 x Ram Type Steering Gear			
+ 100 A5 E3 / G / SOLAS 11 -2, Reg.19 / Multi Purpose Cargo Ship / Strengthened for heavy cargo / Equipped for carriage of containers / Timber deck cargo / Grain cargo / Ice class 1B (FS) / + MC E3 AUT/ Tail -shaft survey / IWS notation / Registry: Netherlands		1 x Transverse Tunnel Bow Thruster, 400 kW			
		Ballast Water Treatment Unit			
		1 x Electrolysis type, Capacity of 500 m3/h			

\*All details believed to be correct and subject to reconfirmation\*



## **CHOWGULE SBD PRIVATE LIMITED**

MANGALURU, KARNATAKA - 575 013, INDIA

W: <a href="https://chowgulesbd.com/">https://chowgulesbd.com/</a>